

# iDISPLAY™ Tablet 10.1" UIT210



The iDISPLAY Tablet 10.1" has been built specifically for commercial use. Operating on an Android operating system and powered by Pulse technology, this display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor Vesa bracket - and just turn on the power. A fully interactive commercial display (with built in WiFi) and a host of integrated features, in either landscape or portrait format. Consumers are automatically restricted to viewing your own content. With the option to expand 3G\* services via a PCIE modem (inserted in the secure back cover), this is a superior alternative to consumer tablets and the ideal touch display for any commercial location.



\*3G Optional, Pending carrier compatibility/availability.  
For more information about iDISPLAY Tablets please  
visit our website: [www.outform.com/idisplay](http://www.outform.com/idisplay)

**OUTFORM™**

Panel Information	Screen Size	10.1"
	Resolution	1280 x 800 Pixels
	Brightness	400 cd/m <sup>2</sup>
	Contrast Ratio	900
	Aspect Ratio	16:9
	Active Area size(HxV)	216.96 x 135.6 mm
	Viewing Angle	80°/80°/80°/80°
	Touch Technology	Capacitive G+G 5 point
Hardware and OS	CPU	RK 3168, 1.2G Dual Core
	Graphics Hardware	RK 616
	Internal Memory	1GB, DDR3
	Flash Memory	8GB Nand flash
	Operating System	Android 4.4 Kit Kat
	Battery	8400mAh (charging: 8 hrs/discharging:8.5 hrs)
Video	Supported Formats	File Format: AVI, MPG, DAT, VOB, DIV, MOV, MKV, MPEG, TS, MTS, M2TS, RM, RMVB, ISO, IFO, WMV, ASF
	Addition Info on Supported Formats	Codec: MPEG1, HD MPEG2 (up to MP@HL), HD MPEG4 SP/ASPH.264 BP@L3, MP & HP@L4.1 Xvid, WMV9/VC-1 AP@L3, RM/RMVB8/9/10 (up to 1080@30P), AVS HD (1920x1080) H.264 Data Rate: up to 60Mbps Resolution: up to 1080p Support TV System: NTSC/PAL Subtitle Support: SRT, SSA, SMI, IDX+SUB
	HDMI Output	Supports (1080p/720p/576p/480p)
	Playback Software	Built-in Software allows for easy setup of a Playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started on boot up.
Audio	Speakers	8 ohm 1W x 2
	Audio Codecs	Supports: Dolby Digital TrueHD, Dolby Digital Plus, DTS HD Master AudioFile Format: MP3, WMA, RA, RM,OGG
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n
	Wired Ethernet	Optional Wired 10/100 Ethernet through the use of a USB adapter.
	GPS	Supports GPS dongle ext (Optional)
	Wireless 3G/4G	Supports Ext Module Mini PCIE (Optional)
General information	Color	Black/White
	Camera	Front 5.0M camera A/F
	I/O ports	DC/Micro SD/HDMI/Earphone/USB2.0 HOST x1/USB 2.0 OTG (Host and Device) x1/ADD ON/PB-Molex
	DC input	9-12v
	Accessories	Power Adapter, User manual, Warranty
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Supply	12V/2.0A
	Power Consumption	14W (max)
	Operation Temperature	0-40 centigrade
	Relative Humidity	0.85
	Certifications	ROHS, FCC and CE Compliant, PSU is also UL, Battery (include the RTC battery) is also UL, UN38.3 compliant
Dimensions	Size (W x D x H)	L261 x W179.6 x D27mm
	Weight	0.85Kg
	Product Carton Size	398 x 222 x 68mm
	Master Carton	414 x 230 x 255mm
	Master Carton Weight	4.5Kg
	Units per Master Carton	3